

BLAST CHILLERS PROBES

Sacet is one of the most important Italian manufacturer of temperature probes for the industrial and commercial refrigeration, air conditioning and heating markets.

PTC, NTC, RTD and THERMOCOUPLES are the main probe types available with various suggested configurations or as required by the customer, intended for plastics, food and automotive industry and for all the applications in which thermoregulation is needed.

The main goal of the company is integrating the production with design/configuration and customization services to ensure customer satisfaction.

The use of solutions, products and processes, reinforced by professional competence and the implementation of the Kaizen Lean principles, ensures the highest quality standard.

Sacet, present both on the Italian and foreign market, is able to reply to customers inquiries with technical and commercial support.



Since 1985 we have been producing probes for all areas of temperature detection and environmental measurements, guaranteeing high quality standards and constantly investing in research and development.



SACET S.R.L.
Via del Candel, 55/D - 32100
Belluno (BL) - Italy
C.F. e P.I. 00654590256

T. +39 0437 33166
E. info@sacet-probes.com



01**02****03****04****05****06****07****08****09****10****11****12****13****14**

PROBE INDEX

- 01 Steel capsule probe with flange
-50°C +110 °C
- 02 Probe with fast steel capsule mm ø4
-50°C +110 °C
- 03 IP68 rubber probe mm ø5x20 rubber capsule
-50°C +110 °C
- 04 IP68 rubber probe mm ø6x20 steel capsule
-50°C +110 °C
- 05 IP68 rubber bracelet probe with clamp
-50°C +110 °C
- 06 IP68 rubber bracelet probe
-50°C +110 °C
- 07 Needle tip probe with 90-degree thermoplastic handle
-50°C +110 °C
- 08 Straight core probe with thermoplastic handle
-50°C +110 °C
- 09 Needle tip probe with 90-degree thermoplastic handle
-50°C +110 °C
- 10 Needle tip probe with 90-degree thermoplastic handle (with heating system)
-50°C +110 °C
- 11 IP67 combined air temperature and humidity probe
-30°C +70 °C
- 12 Automotive connectors
- 13 Overmoulded M12 connectors
- 14 Bracelet probe with metal clamp
-50°C +200 °C